



M4 Printing B.V.
A.Plesmanlaan 13
9615 TJ Kolham
The Netherlands

T +31 (0)598-745082
info@m4printing.com



Technical specifications

PREM.E

Wear layer	EN ISO 24340 / EN 4291		0.20 mm
Total thickness	EN ISO 24346 / EN 428		2.00 mm
Total weight	EN ISO 23997 / EN 430		1250 g/m ²
Standard widths	EN ISO 24341 / EN 426		4 m
Standard length	EN ISO 24341 / EN 426		30 m

			
EN 14041:2004 450-CC0013-1			
			
Expanded (cushioned) polyvinyl chloride floorcoverings			
EN ISO 26986 / EN 653			

Light stability	EN ISO 105 B02		≥ 6
Dimensional Stability	EN ISO 23999 / EN 434		≤ 0.40 %
Underfloor heating	EN 12667		Suitable
Residual Indentation	EN ISO 24343-2 / EN 433		≤ 0.35 mm
Reaction to fire	EN 13501-1		Bfl/S1
Slip resistance	DIN 51130		R10
Dynamic coefficient of friction	EN 13893		> 0.6
Impact sound	EN ISO 717/2		Δ Lw 10 dB

*) Please note that the data given could be imprecise and liable to modifications of a technical nature at any time. The information in these documents is valid from 01/01/2017 and M4Printing B.V. reserve the right to make changes at any moment without prior notice. Our technology is constantly evolving, so before carrying out any projects we encourage you to contact us to maintain our highest level of standards. **) Our products are classified as A+ for the emission of volatile substances inside air. (compulsive sanitary labelling in France since January 2012)